



Testimonials

"In 1995 we purchased the B-Tech monitoring system for each of 5 UPS units with more than 300 batteries in the system for our corporate offices. Since their installation we have not had one battery related outage of an operating UPS unit.

The B-Tech system has fore warned of more than 30 potential battery failures allowing us to replace batteries before they fail...The only way to know how your batteries are performing is to monitor their performance on weekly basis. B-Tech has provided flawless service in maintaining our battery back-up systems."

Ken Rheault, Consumers Energy

S5 Flooded Cell Installation



Find Problem Batteries In Your Switchgear Battery System
BTECH's S5 Series Battery Monitoring and Validation System has been designed specifically for your Switchgear battery system. Our patented and proven impedance measurement technology has the sensitivity required to find failing cells well before they pose a risk to your critical systems. Plus, with battery sensing harnesses pre-designed and tested for your battery system, installation time is cut in half while increasing system reliability.

Why BTECH Is The World Leader In Battery Monitoring
We're Proven: Over 4,000 Systems Installed Worldwide
We're Superior: BTECH's patented impedance method provides rock solid data accuracy and stability, allowing more time to respond - no other system comes close.

We're Non-Destructive: With a load signal optimized to the battery type, our system never subjects your batteries to a stressful load test. Plus, our system is not powered by your batteries.

We Know Your Batteries: With more experience than anyone in the business, our sales and service staff is there for you when you have questions.

Key System Features

- BTECH Monitors Key Battery Parameters: Cell and Inter-cell Impedance, System Voltage, Float, Charge and Discharge Current, plus ambient and pilot cell temperatures
- Impedance measurement spec of 0.1 +/- 0.01 mΩ - the sensitivity required for flooded cells
- Programmable Test & Out-of-Limits Alarms
- Battery Discharge Data Logging
- Up to 520 Individual Cells and 8 Strings per system
- Individual String Current Monitoring for multi-string systems
- Complete Isolation from the Battery String
- No PC Required

Facility Management System Integration

- MODBUS over TCP/IP for simple third-party software integration
- SNMP Capable
- (6) Programmable Output Relays
- (4) Programmable Input Relays

Alarm and Data Acquisition Options

- Local: RS-232 and USB
- Integral Dial Up 56k Modem
- Integral Ethernet Card (Cat 5/6)
- Alarms: Text Message to multiple cell phones, pagers or e-mail addresses, through BVM Software or FMS integration

Safety

- BTECH Quick-Disconnect Safety Fuses simplify battery replacements while protecting personnel during installation and routine maintenance.

